

Cross Roller Bearings / Kreuzrollenlager

XSU Series

No.	Boundary dimension (mm)							Load Rating (N)					Limited Speed	Weight
	di	Da	Di	da	La	Li	na	Fr	Ca	Coa	Cr	Cor	NG rpm	kg
XSU080168	130	205	174	159	190	145	12	8180	66000	240000	42000	96000	227	3.3
XSU080188	150	225	194	179	210	165	16	10900	71000	275000	46000	110000	203	3.7
XSU080218	180	255	224	209	240	195	20	13600	77000	315000	49000	127000	175	4.3
XSU080258	220	295	264	249	280	235	24	26400	84000	375000	54000	151000	148	5.1
XSU080318	280	355	324	309	340	295	28	19100	93000	465000	59000	185000	120	6.3
XSU080398	360	435	404	389	420	375	36	24500	106000	590000	68000	236000	96	7.8

No.	Boundary dimension (mm)								Load Rating (N)					Weight
	di	Da	Di	da	La	Li	na	ni	Fr	Ca	Coa	Cr	Cor	kg
XSU140414	344	484	415	413	460	368	24	24	99100	229000	520000	146000	250000	28
XSU140544	474	614	545	543	590	498	32	32	132200	270000	680000	170000	330000	38
XSU140644	574	714	645	643	690	598	36	36	148700	290000	800000	185000	395000	44
XSU140744	674	814	745	743	790	698	40	40	165200	315000	930000	200000	455000	52
XSU140844	774	914	845	843	890	798	40	40	165200	340000	1050000	215000	510000	60
XSU140944	874	1014	945	943	990	898	44	44	181700	360000	1170000	227000	580000	67
XSU141094	1024	1164	1095	1093	1140	1048	48	48	198200	390000	1360000	246000	670000	77



Sturm Präzision GmbH
 Neckarstraße 47/1
 78727 Oberndorf

Tel. +49 (0) 7423 / 8693 - 0
 Fax +49 (0) 7423 / 8693 - 29
 Internet: www.sturm-precision.de